

Sliding door and forward tilting

T4900 and T41200

Sliding door

- Large door opening for easy loading and unloading
- No space required in front of the dryer for door opening
- Easy to operate

Forward tilting

- Easy unloading – no manual handling
- Rotation of drum while tilting the dryer for easy unloading
- Only available with Sliding door

Frequency controlled motor

- Adjustment of drum speed for correct drop of garments – optimises drying time and saves energy

Indicator lamp for finished drying cycle

- Overview, when finished drying cycle

For technical information regarding the tumble dryers, see datasheet for T4900 and T41200.



Images shown are a representation of the product only and variations may occur.

Shipping data	T4900	T41200
Basic Dryer	545 kg	580 kg
With Sliding Door	599 kg	634 kg
With Sliding Door and tilt	651 kg	686 kg
Heating unit, gas/steam/elect.	39/50/42 kg	46/50/42 kg
Tilt unit	66 kg	66 kg
Dimensions in mm		
A Width	1320	1320
B Depth	1250	1440
C Height	2550	2550
D (with top removed)	1965	1965
E	950	950
F	945	945
G	1360	1360
H	1295	1485
I	2635	2660
K	1565	1755
L	2140	2140
M	410	410
N	1760	1760
O	2435	2435
P	2105	2105
R	570	570

- 1 Control panel
- 2 Door opening \varnothing 940
- 3 Electrical connection
- 4 Gas connection
- 5 Steam connection
- 6 Condensate connection
- 7 Exhaust connection \varnothing 315

Flexible connections to be used for gas/steam and exhaust when installing a dryer with tilt option.

